

Cus	VEHS EIGCUIO LAGA ICHIICC HSC		1/15/1///
	tomer data	Dealer Informat	tion
Add Data Here		Add Data Here	
	Dealer Order Form SN:		
	Original Order Date:		
	Revision Number:	Original Issue	
	Revision Date:	Original locae	
	Estimated Delivery Date EXW Factory:		
	This Price List Valid from:	02/2022	
▼	Insert a "X" in the top column next to the version of aircraft that you wish to add to your order		
х	VELIS ELECTRO SW 128, CS- LSA certified - 600 KG MTOM, DAY VFR, STANDARD CATEGORY AIRPLANE	€ 19	3'000
Х	Air speed indicator 80 mm - 3 1/8" diameter in knot	Incl	uded
Х	Altimeter 80 mm - 3 1/8" diameter in feet (scale in Millibars)	Incl	uded
Х	Vertical Speed Indicator 57 mm - 2 1/4" diameter (with flight timer and clock) in feet/min	Incl	uded
Х	Engine instruments Digital Unit (Pipistrel EPSI 570)	Incl	uded
Х	Radio Funke Avionics ATR 833 with build-in intercom, outside antenna and 2 Pipistrel headsets	Incl	uded
X	Transponder Funke Avionics TRT800 C/S-mode with antenna and installation	Incl	uded
Χ	Digital Artificial Horizon Kanardia Horis 80 mm - 3 1/8" diam		uded
X	Slip skid		uded
X	ELT Artex 345 (406 MHz) - permanently fitted to aircraft	_	uded
Х	AOA based, tactile stall-warning	Incl	uded
L	BASIC ESTIMATED DATA		
L	Estimated useful flight time		es + reserve
L	Estimated battery cycles - 75% of capacity (depend of type of use and charging)		00+
	Upgradable battery packs for future battery technologies		es
	Towing		No
	Night VFR		No
_	Intentional spins		No
-	AIRFRAME	Inol	uded
X	Nose Wheel Model	_	uded
Αχ	Large Instrument Panel Certified 3 blade composite fixed pitch propeller painted in white (front) and black (back)		uded
Ĥ	GENERAL		uucu
Х	35' 1" (10.7 m) wing-span, nose-wheel, two-seater aircraft	Incl	uded
X	Outside surfaces in white, cabin interior composite surfaces in grey		uded
х	Acrylic paint finish outside of aircraft	Included	
х	Cabin upholstery in blue colour with padded spar cover		uaea
			uded
X	Ergonomic rigid seats with adjustable head rest	Incl	
		Incl Incl	uded
Х	Ergonomic rigid seats with adjustable head rest	Incl Incl	uded uded
X	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts	Incl Incl Incl Incl	uded uded uded
X X X	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door	Incl Incl Incl Incl	uded uded uded uded
X X X	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door	Incl Incl Incl Incl Incl Incl	uded uded uded uded uded
x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim	Incl Incl Incl Incl Incl Incl Incl Incl	uded uded uded uded uded uded uded uded
X X X X X X	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot	Incl Incl Incl Incl Incl Incl Incl Incl	uded uded uded uded uded uded uded uded
x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield	Incl	uded uded uded uded uded uded uded uded
X X X X X X	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking	Incl	uded uded uded uded uded uded uded uded
x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x	Incl Incl Incl Incl Incl Incl Incl Incl	uded uded uded uded uded uded uded uded
X X X X X X X X	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6	Incl	uded uded uded uded uded uded uded uded
x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x	Inci	uded uded uded uded uded uded uded uded
x x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6 Hydraulic Beringer differential disk brakes on the main wheels, pedal-mounted levers	Incl Incl Incl Incl Incl Incl Incl Incl	uded uded uded uded uded uded uded uded
x x x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6 Hydraulic Beringer differential disk brakes on the main wheels, pedal-mounted levers Steerable nose wheel with shimmy damper	Incl Incl Incl Incl Incl Incl Incl Incl	uded uded uded uded uded uded uded uded
x x x x x x x x x x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6 Hydraulic Beringer differential disk brakes on the main wheels, pedal-mounted levers Steerable nose wheel with shimmy damper Tie-down points on wings and tail Pipistrel E-811-268MVLC EASA Type Certified 57.6 KW electric liquid cooled engine Pipistrel PB345V119E-L Batteries, installed in a redundant 2-unit arrangement, liquid cooled, total nominal capacity 20.2 kWh. Crashworthy,	Incl	uded uded uded uded uded uded uded uded
x x x x x x x x x x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6 Hydraulic Beringer differential disk brakes on the main wheels, pedal-mounted levers Steerable nose wheel with shimmy damper Tie-down points on wings and tail Pipistrel E-811-268MVLC EASA Type Certified 57.6 KW electric liquid cooled engine Pipistrel PB345V119E-L Batteries, installed in a redundant 2-unit arrangement, liquid cooled, total nominal capacity 20.2 kWh. Crashworthy, thermal-runway inhibiting, HIRF/EMI tolerant	Inci	uded uded uded uded uded uded uded uded
x x x x x x x x x x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6 Hydraulic Beringer differential disk brakes on the main wheels, pedal-mounted levers Steerable nose wheel with shimmy damper Tie-down points on wings and tail Pipistrel E-811-268MVLC EASA Type Certified 57.6 KW electric liquid cooled engine Pipistrel PB345V119E-L Batteries, installed in a redundant 2-unit arrangement, liquid cooled, total nominal capacity 20.2 kWh. Crashworthy, thermal-runway inhibiting, HIRF/EMI tolerant Lightweight High capacity Battery EarthX 680C 12,4Ah	Incl Incl Incl Incl Incl Incl Incl Incl	uded uded uded uded uded uded uded uded
x x x x x x x x x x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6 Hydraulic Beringer differential disk brakes on the main wheels, pedal-mounted levers Steerable nose wheel with shimmy damper Tie-down points on wings and tail Pipistrel E-811-268MVLC EASA Type Certified 57.6 KW electric liquid cooled engine Pipistrel PB345V119E-L Batteries, installed in a redundant 2-unit arrangement, liquid cooled, total nominal capacity 20.2 kWh. Crashworthy, thermal-runway inhibiting, HIRF/EMI tolerant Lightweight High capacity Battery EarthX 680C 12,4Ah USB port in panel pocket	Incl Incl Incl Incl Incl Incl Incl Incl	uded uded uded uded uded uded uded uded
x x x x x x x x x x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6 Hydraulic Beringer differential disk brakes on the main wheels, pedal-mounted levers Steerable nose wheel with shimmy damper Tie-down points on wings and tail Pipistrel E-811-268MVLC EASA Type Certified 57.6 KW electric liquid cooled engine Pipistrel PB345V119E-L Batteries, installed in a redundant 2-unit arrangement, liquid cooled, total nominal capacity 20.2 kWh. Crashworthy, thermal-runway inhibiting, HIRF/EMI tolerant Lightweight High capacity Battery EarthX 680C 12,4Ah USB port in panel pocket Puriplane super efficient surface polishing and protection KIT	Incl Incl Incl Incl Incl Incl Incl Incl	uded uded uded uded uded uded uded uded
x x x x x x x x x x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6 Hydraulic Beringer differential disk brakes on the main wheels, pedal-mounted levers Steerable nose wheel with shimmy damper Tie-down points on wings and tail Pipistrel E-811-268MVLC EASA Type Certified 57.6 KW electric liquid cooled engine Pipistrel PB345V119E-L Batteries, installed in a redundant 2-unit arrangement, liquid cooled, total nominal capacity 20.2 kWh. Crashworthy, thermal-runway inhibiting, HIRF/EMI tolerant Lightweight High capacity Battery EarthX 680C 12,4Ah USB port in panel pocket Puriplane super efficient surface polishing and protection KIT Basic spare parts kit	Incl Incl Incl Incl Incl Incl Incl Incl	uded uded uded uded uded uded uded uded
x x x x x x x x x x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6 Hydraulic Beringer differential disk brakes on the main wheels, pedal-mounted levers Steerable nose wheel with shimmy damper Tie-down points on wings and tail Pipistrel E-811-268MVLC EASA Type Certified 57.6 KW electric liquid cooled engine Pipistrel PB345V119E-L Batteries, installed in a redundant 2-unit arrangement, liquid cooled, total nominal capacity 20.2 kWh. Crashworthy, thermal-runway inhibiting, HIRF/EMI tolerant Lightweight High capacity Battery EarthX 680C 12,4Ah USB port in panel pocket Puriplane super efficient surface polishing and protection KIT Basic spare parts kit AIRCRAFT PRICE	Inci Inci Inci Inci Inci Inci Inci Inci	uded uded uded uded uded uded uded uded
x x x x x x x x x x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6 Hydraulic Beringer differential disk brakes on the main wheels, pedal-mounted levers Steerable nose wheel with shimmy damper Tie-down points on wings and tail Pipistrel FB345V119E-L Batteries, installed in a redundant 2-unit arrangement, liquid cooled, total nominal capacity 20.2 kWh. Crashworthy, thermal-runway inhibiting, HIRF/EMI tolerant Lightweight High capacity Battery EarthX 680C 12,4Ah USB port in panel pocket Puriplane super efficient surface polishing and protection KIT Basic spare parts kit AIRCRAFT PRICE POSSIBLE OPTIONS	Inci Inci Inci Inci Inci Inci Inci Inci	uded uded uded uded uded uded uded uded
x x x x x x x x x x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6 Hydraulic Beringer differential disk brakes on the main wheels, pedal-mounted levers Steerable nose wheel with shimmy damper Tie-down points on wings and tail Pipistrel E-811-268MVLC EASA Type Certified 57.6 KW electric liquid cooled engine Pipistrel PB345V119E-L Batteries, installed in a redundant 2-unit arrangement, liquid cooled, total nominal capacity 20.2 kWh. Crashworthy, thermal-runway inhibiting, HIRF/EMI tolerant Lightweight High capacity Battery EarthX 680C 12,4Ah USB port in panel pocket Puriplane super efficient surface polishing and protection KIT Basic spare parts kit AIRCRAFT PRICE POSSIBLE OPTIONS GPS Garmin Aera 660 or similar + AirGizmo	Inci Inci Inci Inci Inci Inci Inci Inci	uded uded uded uded uded uded uded uded
x x x x x x x x x x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6 Hydraulic Beringer differential disk brakes on the main wheels, pedal-mounted levers Steerable nose wheel with shimmy damper Tie-down points on wings and tail Pipistrel FB345V119E-L Batteries, installed in a redundant 2-unit arrangement, liquid cooled, total nominal capacity 20.2 kWh. Crashworthy, thermal-runway inhibiting, HIRF/EMI tolerant Lightweight High capacity Battery EarthX 680C 12,4Ah USB port in panel pocket Puriplane super efficient surface polishing and protection KIT Basic spare parts kit AIRCRAFT PRICE POSSIBLE OPTIONS	Inci Inci Inci Inci Inci Inci Inci Inci	uded uded uded uded uded uded uded uded
x x x x x x x x x x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the left door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6 Hydraulic Beringer differential disk brakes on the main wheels, pedal-mounted levers Steerable nose wheel with shimmy damper Tie-down points on wings and tail Pipistrel E-811-268MVLC EASA Type Certified 57.6 KW electric liquid cooled engine Pipistrel PB345V119E-L Batteries, installed in a redundant 2-unit arrangement, liquid cooled, total nominal capacity 20.2 kWh. Crashworthy, thermal-runway inhibiting, HIRF/EMI tolerant Lightweight High capacity Battery EarthX 680C 12,4Ah USB port in panel pocket Puriplane super efficient surface polishing and protection KIT Basic spare parts kit AIRCRAFT PRICE POSSIBLE OPTIONS GPS Garmin Aera 660 or similar + AirGizmo EU - Skycharge Solo 22kW, EASA approvied, AS6968 Standard compliant, CE conformity, three phase, 380 Vac, Online features, IP54, 4G Modem, RFID Reader, GB/T Cable, Fix or Mobile; charge time = 60 min. Possible to order it in bundle or as aditional charger. The order,	Incl Incl Incl Incl Incl Incl Incl Incl	uded uded uded uded uded uded uded uded
x x x x x x x x x x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6 Hydraulic Beringer differential disk brakes on the main wheels, pedal-mounted levers Steerable nose wheel with shimmy damper Tie-down points on wings and tail Pipistrel E-811-268MVLC EASA Type Certified 57.6 KW electric liquid cooled engine Pipistrel P845V1195-L Batteries, installed in a redundant 2-unit arrangement, liquid cooled, total nominal capacity 20.2 kWh. Crashworthy, thermal-runway inhibiting, HIRF/EMI tolerant Lightweight High capacity Battery EarthX 680C 12,4Ah USB port in panel pocket Puriplane super efficient surface polishing and protection KIT Basic spare parts kit AIRCRAFT PRICE POSSIBLE OPTIONS GPS Garmin Aera 660 or similar + AirGizmo EU - Skycharge Solo 22kW, EASA approvied, AS6968 Standard compliant, CE conformity, three phase, 380 Vac, Online features, IP54, 4G Modem, RFID Reader, GB/T Cable, Fix or Mobile; charge time = 60 min. Possible to order it in bundle or as aditional charger. The order, delivery and support is made by the Eaton Green Motion. EU - Off-board Charger, 20 kW, EASA approved, not AS6968 compliant, three phase, 380 Vac, 45 - 65 Hz; IP20, charge time approx. 1h Inomin. Possible to order it only with the aircraft, not as aditional charger. The order, delivery and support is made by the Eaton Green Motion.	Incl Incl	uded uded uded uded uded uded uded uded
x x x x x x x x x x x x x x x x x x x	Ergonomic rigid seats with adjustable head rest 4 point "schroth" seat belts Cabin ventilation adjustable intake on the left door Cabin ventilation adjustable intake on the right door Dual control stick, dual rudder pedals 2 stage positive flaperons Electric elevator trim In-flight adjustable pedals for both pilot & co-pilot UV protected, scratch resistant Lexan windshield Three point door locking Fixed composite landing gear, heavy-duty training undercarriage, front "rim size" 3.50 x 4, tire size 4.00 - 4, main landing gear, "rim size" 4.00 x 6, "tire size" 4.00 - 6 Hydraulic Beringer differential disk brakes on the main wheels, pedal-mounted levers Steerable nose wheel with shimmy damper Tie-down points on wings and tail Pipistrel E-811-268MVLC EASA Type Certified 57.6 KW electric liquid cooled engine Pipistrel PB345V119E-L Batteries, installed in a redundant 2-unit arrangement, liquid cooled, total nominal capacity 20.2 kWh. Crashworthy, thermal-runway inhibiting, HIRF/EMI tolerant Lightweight High capacity Battery EarthX 680C 12,4Ah USB port in panel pocket Puriplane super efficient surface polishing and protection KIT Basic spare parts kit AIRCRAFT PRICE POSSIBLE OPTIONS GPS Garmin Aera 660 or similar + AirGizmo EU - Skycharge Solo 22kW, EASA approvied, AS6968 Standard compliant, CE conformity, three phase, 380 Vac, Online features, IP54, 4G Modem, RFID Reader, GBIT Cable, Fix or Mobile; charge time = 60 min. Possible to order it in bundle or as aditional charger. The order, delivery and support is made by Pipistrel.	Incl Incl	uded uded uded uded uded uded uded uded

Wings, tail and fuselage covers in light cloth Closed Trailer dedicated for Electric aicraft transport (increased MTOM)	€ 642	
	€ 31'030	
Simulator Velis X-Alpha VR including Cockpit with cockpit controls, computer, oculus headset and outside monitor	€ 48'150	
Outside liveries standard design in customized colors ()	€ 321	
Registration markings (UV resistant decals) Your registration number is ()	€ 300	
AIRCRAFT PRICE	EURO	€ 193'000
DELIVERY AND DOCUMENTATION		
Export Customs Procedure	€ 100	
Export Documents Outside EU Costs like / EUR 1 / ATR document / Certificate of Origin	€ 130	
Apostille / CAA Certificate of non-registration / Bill of sale document / Notaries authentication	€ 300	
Cost of loading and special supports in the container - Price per aircraft	€ 600	
Cost Of Transport by Road	2,4 EUR/KM	
Transport By Sea	TBC	
Other Documents To Be Done By Request	TBC	
Bureau Veritas Expert Check	TBC	
DELIVERY AND DOCUMENTATION	N EURO	€0
TOTAL EXPORT AIRCRAFT PRICE WITHOUT VA	T EURO	€ 193'000
Please select the following information (Terms of Delivery)		
Terms of Delivery (Incoterms 2010) – DAP (Delivered At Place) (ex DDU)		
Terms of Delivery (Incoterms 2010) – FCA (Free Carrier)		
Terms of Delivery (Incoterms 2010) – EXW (Ex Works) (on special request)		
lease select the following information (GPS Database)		
Americas basemap and Americas database		
International basemap and Atlantic International database		
International basemap and Pacific International database		
Please select the following information		
Compass Hemisphere Information Northern Hemisphere Southern Hemisphere		
Registration Category CS LSA		
ttachments: General terms Pipistrel d.o.o. Ajdovscina		
ave read, accepted and signed this order and attachments as being correct (signature of the customer)		Pipistrel (Signature
······································		
Initial Deposi		€ 50'000.00
Initial Deposi 3 months before delivery 50%		€ 50'000.00 € 96'500.00